



# C80-PR1692 30/70 LED 9000 DALI 830

Glamox C80 is a luminaire solution dedicated for mounting in long lengths. The product is designed especially for LED and is available in pendant, recessed and surface mounted versions.

Item No.	C80P63200
GTIN	4741145242721
Stock status code	X



## Technical specifications

### LMS System

Number of DALI addresses	1
LMS Protocol	DALI

### Completeness

Item is not complete, missing	End caps
-------------------------------	----------

### Light Technical Data

Light source	LED
Lumen Out (lm)	8682
Lumen Per Watt (lm/W)	117
Lamp colour temp (K)	3000
Colour Rendering Index	80
Light Distribution Up %	30
Light Distribution Down %	70
MacAdam step	3
Energy Class Light Source	D

### Driver / Ballast

Type of LED Driver	DALI: Dimming
Number of Driver	1

### Lifetime

LED Lifetime L80B50 Ta25 (h)	70 000
Luminous flux decline (LLMF) 50.000h Ta25	0.85

### Electrical Data

Main Feed AC (V) Min	220
Main Feed AC (V) Max	240
Main Feed Frequency Min	50
Main Feed Frequency Max	60
Total Consumption (W)	74
Number Of Luminaire MCB 10B	13
Number Of Luminaire MCB 10C	22
Number Of Luminaire MCB 16B	21
Number Of Luminaire MCB 16C	35
Leakage Current (mA)	0.46

### Housing

Body Material	Aluminium
Body Colour	Grey
Main Body Colour Name	Grey
Main Body Colour Surface	Anodized

### Dimensions

Length (mm)	1692
Width (mm)	68
Height (mm)	110

### Mounting

Product Mounting	Pendant, Trunking
------------------	-------------------

## Illustrations

